



PROJECT NAME: _____

LOCATION: _____

ITEM: _____ QTY: _____

MODEL: _____

SRF-SC-40/50

SOLID STATE CONTROL TUBE FIRED GAS FRYER

The Sierra all-purpose fryers feature outstanding reliability and durability, capable of cooking a wide variety of fried foods with consistent uniformity and great taste.

Four, highly efficient tube fired, cast iron burners create a large heat-transfer area for reliable, even heat distribution. Our durable temperature probe senses temperature changes and activates a quick burner response. The temperature for the SRF-SC-40/50 ranges from 180°F (82°C) to 375°F (190°C). Includes safety control system.

Every inch of the frypot and cold zone can be cleaned and wiped down by hand. The large cold zone and forward sloping bottom help collect and remove sediment from the frypot to safeguard oil quality and support routine frypot cleaning.

6" swivel casters are optional.

Part #: 119-0021 (Set of 4, 2 locking and 2 non-locking).



TUBE FIRED



Fully peened tank ensures easy cleaning



Solid State Control

STANDARD FEATURES

- 🔥 120,000 BTU's/hr. input.
- 🔥 Large cold zone area.
- 🔥 Delivers heat through 6" x 2" 16-gauge stainless steel heat exchange tubes for even heat transfer and rapid temperature recovery.
- 🔥 1.25" stainless steel full port ball type drain valve.
- 🔥 Stainless steel door is reinforced for added strength with a heavy duty magnetic door catch.
- 🔥 All Stainless Steel cabinet.
- 🔥 Twin fry baskets with plastic coated handles. Stainless steel basket hanger, easily removable for cleaning.
- 🔥 Tank Cleaning Tool Kit consists of: Brush, Scoop & Clean-out Rod.
- 🔥 Behind the door Solid State Control adjusts from 180°F (82°C) to 375°F (190°C) with standing pilot. Includes Melt Cycle, Drain Valve Interlock Switch, Power On/Off Switch.
- 🔥 Hi-limit shut-off protector shuts off gas combination valve and standing pilot.
- 🔥 Built in flue deflector.
- 🔥 Nickel plated tube rack.
- 🔥 Set of four stainless steel adjustable legs.
- 🔥 When placing an order, please specify your preferred configuration; for LP (SRF-SC-40/50 LP) or for Natural gas (SRF-SC-40/50 NG).

SPECIFICATIONS

MODEL NUMBER	SRF-SC-40/50 (NG OR LP)
EXTERNAL DIMENSIONS (WxDxH) INCLUDING HANDLE	15.5" x 31.1" x 45.8"
NUMBER OF BURNERS	4
FRYER CAPACITY	40 - 50 LBS
BTU (EACH BURNER AT 5" W.C.)	30,000
TOTAL BTU	120,000
NET WEIGHT	140 LBS
SHIPPING WEIGHT	158 LBS

